Westerfeldstraße 32-42 32758 Detmold - Germany Telefon: +49 5231 96 07-41 Telefay: +49 5231 96 07-53

Telefax: +49 5231 96 07-53 E-Mail: info@steinbach-ag.de Website: www.steinbach-ag.de



# **Technical Data Sheet**

# **Elastomer 41 Peach**

### **Product description and advantages**

- Area of application: Foil and veneer pressing, Interiors, CFRP/GRP manufacturing
- No contact discolouration on pressed parts
- Long-term flexibility

### Standard dimensions

Width: 1900 mm Material thickness: 2, 3 and 4 mm

Surface: smooth/smooth

Elastomer	TPHN	
Type of rubber	NR – Natural rubber	
Colour	Peach	
Material hardness	41 ± 5 Shore A *	DIN ISO 48-4
Thickness tolerance	± 0.40 mm	
Density/Specific weight	$1.07 \pm 0.05 \text{ g/cm}^3$	DIN EN ISO 1183-1
Tensile strength	15 Mpa	DIN 53 504
Elongation at tear	600 %	DIN 53 504
Rebound resilience	60 %	DIN 53 512
Compression set at: 24h/70°C	35 %	DIN ISO 815 i.A.
Max. temperature	120°C	
•		DIN ISO 815 i.A.

<sup>\*</sup> tested on original material thickness

#### Important information:

The listed test values and data are based on results of many years of development, tests and proving. A characteristics warranty and guaranteed function can't be derived from the information given. It is within the user's responsibility to test the selection of material in a specific application to ascertain his intended operational capability. Technical changes within the product development are subject to change.

edition no.: 1.9\_12032024 current data sheet: see homepage ISO 9001:2015 certified